

WHAT IS CLAIMED IS:

- Sub Q' 1. An edge correction apparatus for a digital video camera, comprising:
- a horizontal edge signal generator and a vertical edge signal generator for respectively generating horizontal and vertical edge correction signals in horizontal and vertical directions of a sensed image obtained via an image sensing element of a digital video camera;
- 10 a horizontal edge signal gain controller and a vertical edge signal gain controller for controlling gains of the horizontal and vertical edge correction signals respectively from said horizontal edge signal generator and said vertical edge signal generator;
- 15 an adder for adding the horizontal and vertical edge correction signals whose gains are controlled by said horizontal edge signal gain controller and said vertical edge signal gain controller;
- a slice processor for adding, to an image processing signal of the digital video camera, an edge correction signal obtained by performing slice processing for an edge signal output from said adder; and
- 20 a vertical edge component suppression position detector for causing said vertical edge signal gain controller to execute gain control of the vertical edge
- 25

SEARCHED SERIALIZED INDEXED

correction signal in accordance with a horizontal difference signal output from said horizontal edge signal generator.

2. An apparatus according to claim 1, wherein the
5 horizontal difference signal is a signal corresponding to
a luminance difference between horizontally adjacent
pixels that is output from said horizontal edge signal
generator.

3. An apparatus according to claim 1, wherein the
10 horizontal difference signal is a signal corresponding to
an output difference in green signal between horizontally
adjacent pixels that is output from said horizontal edge
signal generator.

4. An apparatus according to claim 1, wherein the
15 horizontal difference signal is a signal corresponding to
a luminance difference between horizontally adjacent
pixels that is output from said horizontal edge signal
generator and a difference between digital video camera
CCD output signals vertically adjacent at the same pixel
20 position.

5. An apparatus according to claim 1, wherein the horizontal difference signal is a signal corresponding to an output difference in green signal between horizontally adjacent pixels that is output from said horizontal edge signal generator and a difference between digital video

camera CCD output signals vertically adjacent at the same pixel position.

6. An apparatus according to claim 1, wherein gain control of the vertical edge correction signal by said vertical edge signal gain controller is executed when an amplitude of the horizontal difference signal exceeds a set threshold.

7. An apparatus according to claim 2, wherein gain control of the vertical edge correction signal by said vertical edge signal gain controller is executed when the luminance difference between horizontally adjacent pixels is not less than a set threshold.

8. An apparatus according to claim 3, wherein gain control of the vertical edge correction signal by said vertical edge signal gain controller is executed when the output difference in green signal between horizontally adjacent pixels is not less than a set threshold.

9. An apparatus according to claim 4, wherein gain control of the vertical edge correction signal by said vertical edge signal gain controller is executed when the luminance difference between horizontally adjacent pixels is not less than a set threshold, and outputs of vertically adjacent digital video camera CCD output signals are not more than the set threshold.

25 10. An apparatus according to claim 5, wherein gain

control of the vertical edge correction signal by said vertical edge signal gain controller is executed when the output difference in green signal between horizontally adjacent pixels is not less than a set threshold, and the 5 difference between vertically adjacent digital video camera CCD output signals is not more than the set threshold.